

Innovative S

YAGEO

DATA SHEET

HIGH VOLTAGE CHIP RESISTORS

0.5%, 1%, 5%

RoHS compliant



YAGEO
Phycomp

Product specification – August 27, 2015 V.5



SCOPE

This specification describes RV0603/0805/1206/2010/2512 high voltage chip resistors with lead-free terminations made by thick film process.

APPLICATIONS

- Converter
- Printer equipment
- Battery charger
- Computer
- Power supply

FEATURES

- RoHS compliant
- Reducing environmentally hazardous wastes
- High component and equipment reliability
- Non-forbidden materials used in products/production
- Halogen Free Epoxy
-

ORDERING INFORMATION – GLOBAL PART NUMBER & 12NC

Both part numbers are identified by the series, size, tolerance, packing type, temperature coefficient, taping reel and resistance value.

	(1)	(2)	(3)	(4)	(5)	(6)	(7)
(1) SIZE	0603/0805/1206/2010/2512						
(2) TOLERANCE	D = ±0.5% F = ±1% J = ±5%						
(3) PACKAGING TYPE	R = Paper/PE taping reel K = Embossed taping reel						
(4) TEMPERATURE COEFFICIENT OF RESISTANCE	– = Base on spec						
(5) TAPING REEL	07= 7 inch dia. Reel						
(6) RESISTANCE VALUE	There are 2~4 digits indicated the resistor value. Letter R/K/M is decimal point, no need to mention the last zero after R/K/M, e.g.1K2, not 1K20. Detailed resistance rules show in table of “Resistance rule of global part number”.						
(7) DEFAULT CODE	Letter L is system default code for ordering only ^(Note)						



Both GLOBAL PART NUMBER (preferred) and 12NC (traditional) codes are acceptable to order Phycomp brand products.

For detailed information of GLOBAL PART NUMBER and ordering example, please refer to page 2.

SIZE	TYPE	START IN ⁽¹⁾	TOL. (%)	RESISTANCE RANGE	(2)	(3)	(4)	Last digit of 12NC Resistance decade ⁽³⁾	
								EMBOSSED ⁽²⁾ TAPE ON REEL	PAPER/PE ⁽²⁾ TAPE ON REEL (units)
0805	VRC11	2322	±5%	47 to 10M Ω	-			0.01 to 0.0976 Ω	0
	VRC12	2322	±1%	47 to 10M Ω	-			0.1 to 0.976 Ω	7
1206	VRC01	2322	±5%	47 to 27M Ω	-			1 to 9.76 Ω	8
	VRC02	2322	±1%	47 to 10M Ω	-			10 to 97.6	9
2512	VPRC221	2322	±5%	47 to 16M Ω	762	98xxx	-	100 to 976	1
								1 to 9.76 K	2
								10 to 97.6 K	3
								100 to 976 K	4
								1 to 9.76 M	5
								10 to 97.6 M	6

- (1) The resistors have a 12-digit ordering code starting with 2322.
- (2) The subsequent 4 or 5 digits indicate the resistor tolerance and packaging.
- (3) The remaining 4 or 3 digits represent the resistance value with the last digit indicating the multiplier as shown in the table of "Last digit of 12NC".
- (4) "L" is optional symbol (Note).

Example:	0.02	=	0200 or 200
	0.3	=	3007 or 307
	1	=	1008 or 108
	33 K	=	3303 or 333
	10 M	=	1006 or 106

The ordering code of a VRC01 resistor, value 1 M with ±5% tolerance, supplied in tape of 5,000 units per reel is: 232279061105L or RV1206JR-071ML.

- 1. All our R-Chip products are RoHS compliant. "LFP" of the internal 2D reel label mentions "Lead Free Process"
- 2. On customized label, "LFP" or specific symbol printed and the optional "L" at the end of GLOBAL PART NUMBER / 12NC can be added (both are on customer request)




MARKING

RV0603/0805/1206/2010/2512



E-24 series: 3 digits, $\pm 5\%$
First two digits for significant figure and 3rd digit for number of zeros

RV0603




E-24 series: 3 digits, $\pm 0.5\%$ & $\pm 1\%$
One short bar under marking letter



E-96 series: 3 digits, $\pm 0.5\%$ & $\pm 1\%$
First two digits for E-96 marking rule and 3rd letter for number of zeros

RV0805/1206/2010/2512



Both E-24 and E-96 series: 4 digits, $\pm 0.5\%$ & $\pm 1\%$
First three digits for significant figure and 4th digit for number of zeros

For further marking information, please refer to data sheet “Chip resistors marking”.


CONSTRUCTION

The resistor is constructed on top of a high-grade ceramic body. Internal metal electrodes are added on each end to make the contacts to the thick film resistive element. The composition of the resistive element is a noble metal imbedded into a glass and covered by a second glass to prevent environment influences. The resistor is laser trimmed to the rated resistance value. The resistor is covered with a protective epoxy coat, finally the two external terminations (matte tin on Ni-barrier) are added. See fig.5

DIMENSIONS

Table 1 For outlines see fig. 5

TYPE	L (mm)	W (mm)	H (mm)	l_1 (mm)	l_2 (mm)
RV0603	1.60 \pm 0.10	0.80 \pm 0.10	0.45 \pm 0.10	0.25 \pm 0.15	0.25 \pm 0.15
RV0805	2.00 \pm 0.10	1.25 \pm 0.10	0.50 \pm 0.10	0.35 \pm 0.20	0.35 \pm 0.20
RV1206	3.10 \pm 0.10	1.60 \pm 0.10	0.55 \pm 0.10	0.40 \pm 0.20	0.45 \pm 0.20
RV2010	5.00 \pm 0.10	2.50 \pm 0.15	0.55 \pm 0.10	0.45 \pm 0.15	0.50 \pm 0.20
RV2512	6.35 \pm 0.10	3.10 \pm 0.15	0.55 \pm 0.10	0.60 \pm 0.20	0.50 \pm 0.20




ELECTRICAL CHARACTERISTICS

Table 2

TYPE	RESISTANCE RANGE	Rated Power	Operating Temperature Range	CHARACTERISTICS				
				Max. Working Voltage	Max. Overload Voltage	Dielectric Withstanding Voltage	Temperature Coefficient of Resistance	
RV0603	5% (E-24) 47Ω to 10MΩ	1/10W			350V	500V	500V	
	1% (E-24/E-96) 47Ω to 10MΩ							
	0.5% (E-24/E-96) 47Ω to 10MΩ							
RV0805	5% (E-24) 47Ω to 22MΩ	1/8 W			400 V	800 V	800 V	
	1% (E-24/E-96) 47Ω to 22MΩ							
	0.5% (E-24/E-96) 47Ω to 10MΩ							
RV1206	5% (E-24) 47Ω to 27MΩ	1/4 W	-55 °C to +155 °C		500 V	1,000 V	1,000 V	±200 ppm/°C
	1% (E-24/E-96) 47Ω to 27MΩ							
	0.5% (E-24/E-96) 47Ω to 10MΩ							
RV2010	5% (E-24) 47Ω to 22MΩ	3/4W			500 V	1,000 V	1,000 V	
	1% (E-24/E-96) 47Ω to 22MΩ							
	0.5% (E-24/E-96) 47Ω to 10MΩ							
RV2512	5% (E-24) 47Ω to 16MΩ	1 W			500 V	1,000 V	1,000 V	
	1% (E-24/E-96) 47Ω to 16MΩ							
	0.5% (E-24/E-96) 47Ω to 10MΩ							

FOOTPRINT AND SOLDERING PROFILES

For recommended footprint and soldering profiles, please refer to data sheet “Chip resistors mounting”.

PACKING STYLE AND PACKAGING QUANTITY

Table 3 Packing style and packaging quantity

PACKING STYLE	REEL DIMENSION	RV0603	RV0805	RV1206	RV2010	RV2512
Paper/PE taping reel (R)	7" (178 mm)	5,000	5,000	5,000	---	---
Embossed taping reel (K)	7" (178 mm)	---	---	---	4,000	4,000

1. For Paper/PE/Embossed tape and reel specification/dimensions, please refer to data sheet “Chip resistors packing”.



FUNCTIONAL DESCRIPTION

Range: -55 °C to +155 °C

Each type rated power at 70 °C:
 RV0603=1/10W; RV0805=1/8W; RV1206=1/4W;
 RV2010=3/4W; RV2512=1W

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V = \sqrt{(P \times R)}$$

or max. working voltage whichever is less


Where

V = Continuous rated DC or AC (rms) working voltage (V)

P = Rated power (W)

R = Resistance value (Ω)

Maximum working voltage can be applicable to resistors only if the resistance value is equal to or higher than the critical resistance value.





TESTS AND REQUIREMENTS

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS
Life/ Operational Life/ Endurance	MIL-STD-202G-method 108A IEC 60115-1 4.25.1 JIS C 5202-7.10	1,000 hours at 70±5 °C applied RCWV 1.5 hours on, 0.5 hour off, still air required	±(2%+0.05 Ω)
High Temperature Exposure/ Endurance at upper category temperature	MIL-STD-202G-method 108A IEC 60115-1 4.25.3 JIS C 5202-7.11	1,000 hours at maximum operating temperature depending on specification, unpowered No direct impingement of forced air to the parts Tolerances: 155±3 °C	±(1%+0.05 Ω)
Moisture Resistance	MIL-STD-202G-method 106F IEC 60115-1 4.24.2	Each temperature / humidity cycle is defined at 8 hours (method 106F), 3 cycles / 24 hours for 10d with 25 °C / 65 °C 95% R.H, without steps 7a & 7b, unpowered Parts mounted on test-boards, without condensation on parts Measurement at 24±2 hours after test conclusion	±(2%+0.05 Ω)
Thermal Shock	MIL-STD-202G-method 107G	-55/+125 °C Note: Number of cycles required is 300. Maximum transfer time is 20 seconds. Dwell time is 15 minutes. Air – Air	±(0.5%+0.05 Ω) for 10 KΩ to 10 MΩ ±(1%+0.05 Ω) for others
Short time overload	MIL-R-55342D-para 4.7.5 IEC60115-1 4.13	2.5 times RCWV or maximum overload voltage whichever is less for 5 sec at room temperature	±(2%+0.05 Ω) No visible damage



TEST	TEST METHOD	PROCEDURE	REQUIREMENTS
Solderability - Wetting	IPC/JEDECJ-STD-002B test B IEC 60068-2-58	Electrical Test not required Magnification 50X SMD conditions: 1 st step: method B, aging 4 hours at 155 °C dry heat 2 nd step: leadfree solder bath at 245±3 °C Dipping time: 3±0.5 seconds	Well tinned (≥95% covered) No visible damage
- Leaching	IPC/JEDECJ-STD-002B test D IEC 60068-2-58	Leadfree solder, 260 °C, 30 seconds immersion time	No visible damage
- Resistance to Soldering Heat	MIL-STD-202G-method 210F IEC 60068-2-58	Condition B, no pre-heat of samples Leadfree solder, 260 °C, 10 seconds immersion time Procedure 2 for SMD: devices fluxed and cleaned with isopropanol	±(1%+0.05 Ω) No visible damage

**REVISION HISTORY**

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Version 5	Aug. 27, 2015	-	- Extend resistor range and add 0.5%
Version 4	Jan. 27, 2014	-	- RV0603 resistance range extend to 10M - Add RV2010
Version 3	Aug. 26, 2013	-	- Add RV0603
Version 2	Sep 29, 2011	-	- Type error correction
Version 1	Nov 19, 2008	-	- Change to dual brand datasheet that describes RV0805/1206/2512 with RoHS compliant - Description of "Halogen Free Epoxy" added - Define global part number
Version 0	Feb 14, 2006	-	- New datasheet for high voltage chip resistors sizes of 0805/1206/2512, 5%, 1% tolerance with lead-free terminations - Replace the 0805/1206/2512 parts of pdf files: VRC01_02_11_12_51_3.pdf, VPRC221_5_3.pdf, and combine into a document. - Test method and procedure updated - PE tape added (paper tape will be replaced by PE tape)

"Yageo reserves all the rights for revising the content of this datasheet without further notification, as long as the products itself are unchanged. Any product change will be announced by PCN."